

2G Produktübersicht Biogas

Typ	Konfiguration	Leistung elektrisch	Wirkungsgrad			
			thermisch	elektrisch	thermisch	gesamt
patruus 50	ct80-0	50 kW	70 kW	35,40%	49,80%	85,20%
patruus 64	ct80-0	64 kW	85 kW	36,30%	48,10%	84,40%
filius 104	ct80-0	50 kW	70 kW	35,40%	49,80%	85,20%
filius 204	ct80-0	64 kW	85 kW	36,30%	48,10%	84,40%
filius 404	at135-0*	75 (80) kW	85 kW	38,00%	43,00%	81,00%
	bt135-0	100 kW	110 kW	38,60%	42,40%	81,00%
	ct135-0	160 kW	155 kW	41,50%	40,20%	81,70%
agenitor 404	at135-0*	75 kW	85 kW	38,00%	43,00%	81,00%
	bt135-0	100 kW	110 kW	38,60%	42,40%	81,00%
	ct135-0	160 kW	155 kW	41,50%	40,20%	81,70%
agenitor 406	ct135-0	250 kW	245 kW	42,50%	41,60%	84,10%
agenitor 408	ct135-0	360 kW	345 kW	42,50%	40,70%	83,20%
agenitor 412	ct135-0	450 kW	468 kW	41,10%	42,70%	83,80%

Typ	Leistung* elektrisch	Wirkungsgrad			
		thermisch	elektrisch	thermisch	gesamt
avus 500a	550 kW	567 kW	41,60%	42,90%	84,50%
avus 500 plus	550 kW	526 kW	42,50%	40,60%	83,10%
avus 500c	600 kW	602 kW	41,60%	41,80%	83,50%
avus 500b	637 kW	702 kW	40,50%	44,70%	85,20%
avus 800c	800 kW	799 kW	41,80%	41,70%	83,50%
avus 800a	851 kW	921 kW	40,70%	44,00%	84,70%
avus 800b	901 kW	904 kW	42,30%	42,40%	84,70%
avus 1000a	1.067 kW	1.165 kW	40,90%	44,70%	85,60%
avus 1000c	1.200 kW	1.178 kW	42,50%	41,70%	84,20%
avus 1000b	1.203 kW	1.201 kW	42,50%	42,40%	84,90%
avus 1500b	1.501 kW	1.500 kW	42,40%	42,40%	84,80%
avus 1500c	1.560 kW	1.564 kW	42,00%	42,10%	84,10%
avus 2000c	2.000 kW	1.984 kW	42,60%	42,20%	84,80%